

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
 Revision Date: 12/15/2014 Date of issue: 10/28/2014

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Aluminum Alloys

**Synonyms:** Al

#### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** No use is specified.

#### 1.3. Name, Address, and Telephone of the Responsible Party

Ductmate Industries Inc  
 210 5th Street  
 Charleroi, PA  
 15022  
 TEL: 1-800-245-3188

#### 1.4. Emergency Telephone Number

**Emergency Number:** ChemTel Inc: 1-800-255-3924, +1 (813)-248-0585

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

**Classification (GHS-US)**

Not classified

#### 2.2. Label Elements

**GHS-US Labeling** No labeling applicable

#### 2.3. Other Hazards

This product is present in a massive form as an alloy. It does not present the same hazards when the individual components are in their powdered forms. The materials present in this product in their powdered forms present aquatic toxicity to the environment, pyrophoricity, flammability, self-heating capabilities, carcinogenicity, water reactivity, and acute toxicity. When processed or where dust is generated a combustible dust hazard may be present. Avoid generating dust, generating sparks, ignition sources, and take all precautions.

Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Under normal use and handling of the solid form of this material there are few health hazards. Cutting, welding, melting, grinding etc. of these materials will produce dust, fume or particulate containing the component elements of these materials. Exposure to the dust, fume or particulate of these materials may present significant health hazards. Exposure to dust or fume may cause irritation of the eyes, skin and respiratory tract. Fine particulates dispersed in air may present an explosion hazard.

#### 2.4. Unknown Acute Toxicity (GHS-US) No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

Not applicable

| Name     | Product Identifier | % (w/w)                | Classification (GHS-US)   |
|----------|--------------------|------------------------|---|
| Aluminum | (CAS No) 7429-90-5 | 80 - 99.7              | Comb. Dust<br>Flam. Sol. 1, H228<br>Water-react. 2, H261                                      |
| Silicon  | (CAS No) 7440-21-3 | 10 - 20                | Comb. Dust  |
| Copper   | (CAS No) 7440-50-8 | 1 - 5, 5 - 10, 10 - 20 | Comb. Dust<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412                                |
| Cobalt   | (CAS No) 7440-48-4 | 0.1 - 1, 1 - 5, 5 - 10 | Acute Tox. 4 (Oral), H302<br>Acute Tox. 1 (Inhalation:dust,mist), H330<br>Eye Irrit. 2A, H319 |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|            |                    |                            |   |
|------------|--------------------|----------------------------|---|
|            |                    |                            | Resp. Sens. 1B, H334<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>Repr. 2, H361<br>Aquatic Acute 3, H402<br>Aquatic Chronic 1, H410  |
| Zinc oxide | (CAS No) 1314-13-2 | 1 - 5, 5 -10               | Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  |
| Tin        | (CAS No) 7440-31-5 | 1 - 5, 5 -10               | Comb. Dust  |
| Manganese  | (CAS No) 7439-96-5 | 1 - 5, 5 -10               | Comb. Dust  |
| Lead       | (CAS No) 7439-92-1 | 1 - 5, 5 -10               | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Inhalation:dust,mist), H332<br>Carc. 1B, H350<br>Repr. 1A, H360<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| Nickel     | (CAS No) 7440-02-0 | < 0.1, 0.1 -<br>1, 1 - 2.4 | Skin Sens. 1, H317<br>Carc. 2, H351<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412  |
| Silver     | (CAS No) 7440-22-4 | 0.1 - 1                    | Eye Irrit. 2A, H319<br>STOT SE 3, H335<br>Aquatic Acute 1, H400   |

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**General:** IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an unconscious person.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Cool skin rapidly with cold water after contact with molten product. Removal of solidified molten material from skin requires medical assistance. Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists.

**Eye Contact:** Removal of solidified molten material from the eyes requires medical assistance. Immediately rinse with water for a prolonged period (at least 15 minutes) while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Welding, cutting, or processing this material may release dust or fumes that are hazardous.

**Inhalation:** Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

**Skin Contact:** May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

**Eye Contact:** Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Chronic Symptoms:** In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Manganese : Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Silicon : Can cause chronic bronchitis and narrowing of the airways. Lead: Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Zinc: Prolonged exposure to high concentrations of zinc fumes may cause "zinc shakes", an involuntary twitching of the muscles. Otherwise, zinc is non-toxic. Tin: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis", a mild form of pneumoconiosis. Silver: Chronic skin contact or ingestion of silver dust, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire. Dry sand; Class D Extinguishing Agent (for metal powder fires).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Do not use water when molten material is involved, may react violently or explosively on contact with water.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** A non-combustible material, not considered flammable but will melt above 1215 °F (657.2 °C).

**Explosion Hazard:** In molten state: reacts violently with water (moisture).

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Under fire conditions, hazardous fumes will be present.

**Firefighting Instructions:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Oxides of tin. Oxides of nickel. Oxides of copper. Oxides of silicone and carbon. Oxides of lead. Oxides of aluminum. Oxides of silver.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not handle until all safety precautions have been read and understood. Do not breathe vapors from molten product. Avoid all eye and skin contact and do not breathe dust, fumes, and vapors.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain and collect as any solid.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. For particulates and dust: Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use PPE described in Section 8. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up.

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### 6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** May generate flammable/explosive dusts or turnings when brushed, machined or ground. Use care during processing to minimize generation of dust. Where excessive dust may result, use approved respiratory protection equipment. Heating of product can release toxic or irritating fumes; ensure proper ventilation is employed, proper precautions are enforced, and applicable regulations are followed. Inhalation of fumes may cause metal fume fever.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Water, humidity. Corrosive substances in contact with metals may produce flammable hydrogen gas.

### 7.3. Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

| Aluminum (7429-90-5)    |                                      |  |
|-------------------------|--------------------------------------|--|
| Mexico                  | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (dust)  |
| USA ACGIH               | ACGIH TWA (mg/m <sup>3</sup> )       | 1 mg/m <sup>3</sup> (respirable fraction)                                      |
| USA OSHA                | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction) |
| USA NIOSH               | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable dust)     |
| Alberta                 | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (dust)  |
| British Columbia        | OEL TWA (mg/m <sup>3</sup> )         | 1.0 mg/m <sup>3</sup> (respirable)   |
| Manitoba                | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (respirable fraction)                                      |
| New Brunswick           | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (metal dust)  |
| Newfoundland & Labrador | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (respirable fraction)                                      |
| Nova Scotia             | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (respirable fraction)                                      |
| Nunavut                 | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Nunavut                 | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Northwest Territories   | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Northwest Territories   | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Ontario                 | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (respirable)   |
| Prince Edward Island    | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (respirable fraction)                                      |
| Québec                  | VEMP (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| Saskatchewan            | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup> (dust)  |
| Saskatchewan            | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (dust)  |
| Silicon (7440-21-3)     |                                      |  |
| Mexico                  | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (inhalable fraction)                                      |
| Mexico                  | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| USA OSHA                | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction) |
| USA NIOSH               | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable dust)     |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                              |                               |   |
|------------------------------|-------------------------------|---|
| <b>British Columbia</b>      | OEL TWA (mg/m <sup>3</sup> )  | 10 mg/m <sup>3</sup> (total dust)   |
| <b>New Brunswick</b>         | OEL TWA (mg/m <sup>3</sup> )  | 10 mg/m <sup>3</sup>  |
| <b>Nunavut</b>               | OEL TWA (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup> (respirable mass)   |
| <b>Northwest Territories</b> | OEL TWA (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup> (respirable mass)   |
| <b>Ontario</b>               | OEL TWA (mg/m <sup>3</sup> )  | 10 mg/m <sup>3</sup> (total dust)   |
| <b>Québec</b>                | VEMP (mg/m <sup>3</sup> )     | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust) |
| <b>Saskatchewan</b>          | OEL STEL (mg/m <sup>3</sup> ) | 20 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>          | OEL TWA (mg/m <sup>3</sup> )  | 10 mg/m <sup>3</sup>  |
| <b>Yukon</b>                 | OEL STEL (mg/m <sup>3</sup> ) | 20 mg/m <sup>3</sup>  |
| <b>Yukon</b>                 | OEL TWA (mg/m <sup>3</sup> )  | 30 mppcf  |

### Copper (7440-50-8)

|                                    |                                      |   |
|------------------------------------|--------------------------------------|---|
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)<br>1 mg/m <sup>3</sup> (dust and mist) |
| <b>Mexico</b>                      | OEL STEL (mg/m <sup>3</sup> )        | 2 mg/m <sup>3</sup> (fume)<br>2 mg/m <sup>3</sup> (dust and mist)   |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )       | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (fume)<br>1 mg/m <sup>3</sup> (dust and mist) |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 1 mg/m <sup>3</sup> (dust and mist)<br>0.1 mg/m <sup>3</sup> (fume) |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )         | 100 mg/m <sup>3</sup> (dust, fume and mist)                         |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (dust and mist)                                 |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )        | 0.6 mg/m <sup>3</sup> (fume)  |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )        | 0.6 mg/m <sup>3</sup> (fume)  |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )        | 0.6 mg/m <sup>3</sup> (fume)  |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> )        | 0.2 mg/m <sup>3</sup> (fume)  |
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )         | 0.2 mg/m <sup>3</sup> (fume)  |

### Cobalt (7440-48-4)

|                                    |                                      |  |
|------------------------------------|--------------------------------------|--|
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (dust and fume)  |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )       | 0.02 mg/m <sup>3</sup>                 |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (dust and fume)  |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.05 mg/m <sup>3</sup> (dust and fume) |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )         | 20 mg/m <sup>3</sup> (dust and fume)   |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )         | 0.02 mg/m <sup>3</sup>                 |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                    |  |  |
|------------------------------------|--|--|
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )            | 0.3 mg/m <sup>3</sup> (dust and fume)  |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )             | 0.1 mg/m <sup>3</sup> (metal-dust and fume)  |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )            | 0.3 mg/m <sup>3</sup> (dust and fume)  |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )             | 0.1 mg/m <sup>3</sup> (dust and fume)  |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )             | 0.02 mg/m <sup>3</sup>   |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )             | 0.02 mg/m <sup>3</sup>   |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )                | 0.02 mg/m <sup>3</sup>   |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )            | 0.06 mg/m <sup>3</sup>   |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )             | 0.02 mg/m <sup>3</sup>   |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> )            | 0.15 mg/m <sup>3</sup> (dust and fume)   |
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )             | 0.05 mg/m <sup>3</sup> (dust and fume)   |
| <b>Zinc oxide (1314-13-2)</b>      |  |  |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )             | 5 mg/m <sup>3</sup> (fume)<br>10 mg/m <sup>3</sup> (dust)  |
| <b>Mexico</b>                      | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (fume)  |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )           | 2 mg/m <sup>3</sup> (respirable fraction)  |
| <b>USA ACGIH</b>                   | ACGIH STEL (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup> (respirable fraction)   |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup> (fume)<br>15 mg/m <sup>3</sup> (total dust)<br>5 mg/m <sup>3</sup> (respirable fraction) |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> )     | 5 mg/m <sup>3</sup> (dust and fume)  |
| <b>USA NIOSH</b>                   | NIOSH REL (STEL) (mg/m <sup>3</sup> )    | 10 mg/m <sup>3</sup> (fume)  |
| <b>USA NIOSH</b>                   | NIOSH REL (ceiling) (mg/m <sup>3</sup> ) | 15 mg/m <sup>3</sup> (dust)  |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )             | 500 mg/m <sup>3</sup>  |
| <b>Alberta</b>                     | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable)  |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable)   |
| <b>British Columbia</b>            | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable)  |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable)   |
| <b>Manitoba</b>                    | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable fraction)  |
| <b>New Brunswick</b>               | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (fume)  |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )             | 10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica, dust)            |
| <b>Newfoundland &amp; Labrador</b> | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable fraction)  |
| <b>Nova Scotia</b>                 | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable fraction)  |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (fume)  |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )             | 5 mg/m <sup>3</sup> (fume)   |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (fume)  |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )             | 5 mg/m <sup>3</sup> (fume)   |
| <b>Ontario</b>                     | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable)  |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable)   |
| <b>Prince Edward Island</b>        | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (respirable fraction)  |
| <b>Québec</b>                      | VECD (mg/m <sup>3</sup> )                | 10 mg/m <sup>3</sup> (fume)  |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )                | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust)                          |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (dust and fume, respirable fraction)  |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )             | 2 mg/m <sup>3</sup> (dust and fume, respirable fraction)   |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (fume)  |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                    |   |  |
|------------------------------------|---|--|
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )            | 5 mg/m <sup>3</sup> (fume)   |
| <b>Tin (7440-31-5)</b>             |   |  |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Mexico</b>                      | OEL STEL (mg/m <sup>3</sup> )           | 4 mg/m <sup>3</sup>  |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )          | 2 mg/m <sup>3</sup>  |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> )    | 2 mg/m <sup>3</sup>  |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )            | 100 mg/m <sup>3</sup>  |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )               | 2 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )           | 4 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>  |
| <b>Manganese (7439-96-5)</b>       |   |  |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup><br>1 mg/m <sup>3</sup> (fume)  |
| <b>Mexico</b>                      | OEL STEL (mg/m <sup>3</sup> )           | 3 mg/m <sup>3</sup> (fume)   |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )          | 0.02 mg/m <sup>3</sup> (respirable fraction)<br>0.1 mg/m <sup>3</sup> (inhalable fraction) |
| <b>USA OSHA</b>                    | OSHA PEL (Ceiling) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> (fume)   |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> )    | 1 mg/m <sup>3</sup> (fume)   |
| <b>USA NIOSH</b>                   | NIOSH REL (STEL) (mg/m <sup>3</sup> )   | 3 mg/m <sup>3</sup>  |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )            | 500 mg/m <sup>3</sup>  |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup>  |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup>  |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )            | 0.02 mg/m <sup>3</sup> (respirable fraction)   |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup>  |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )            | 0.02 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )            | 0.02 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Nunavut</b>                     | OEL Ceiling (mg/m <sup>3</sup> )        | 5 mg/m <sup>3</sup>  |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )           | 3 mg/m <sup>3</sup> (fume)   |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )            | 1 mg/m <sup>3</sup> (fume)   |
| <b>Northwest Territories</b>       | OEL Ceiling (mg/m <sup>3</sup> )        | 5 mg/m <sup>3</sup>  |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )           | 3 mg/m <sup>3</sup> (fume)   |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )            | 1 mg/m <sup>3</sup> (fume)   |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup>  |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )            | 0.02 mg/m <sup>3</sup> (respirable fraction)   |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )               | 0.2 mg/m <sup>3</sup> (total dust and fume)  |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )           | 0.6 mg/m <sup>3</sup>  |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )            | 0.2 mg/m <sup>3</sup>  |
| <b>Yukon</b>                       | OEL Ceiling (mg/m <sup>3</sup> )        | 5 mg/m <sup>3</sup>  |
| <b>Lead (7439-92-1)</b>            |   |  |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )            | 0.15 mg/m <sup>3</sup> (dust and fume)   |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )          | 0.05 mg/m <sup>3</sup>   |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )     | 50 µg/m <sup>3</sup>   |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> )    | 0.050 mg/m <sup>3</sup>  |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                    |                                      |   |
|------------------------------------|--------------------------------------|---|
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )         | 100 mg/m <sup>3</sup>                                     |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )        | 0.45 mg/m <sup>3</sup>                                    |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.15 mg/m <sup>3</sup>                                    |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )        | 0.45 mg/m <sup>3</sup>                                    |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )         | 0.15 mg/m <sup>3</sup>                                    |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup> (designated substances regulation) |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )            | 0.05 mg/m <sup>3</sup>                                    |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )        | 0.15 mg/m <sup>3</sup>                                    |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> )        | 0.45 mg/m <sup>3</sup> (dust and fume)                    |
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )         | 0.15 mg/m <sup>3</sup> (dust and fume)                    |
| <b>Nickel (7440-02-0)</b>          |                                      |   |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup>                                       |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )       | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 1 mg/m <sup>3</sup>                                       |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.015 mg/m <sup>3</sup>                                   |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>                                      |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup>                                     |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>                                    |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup>                                       |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> )        | 2 mg/m <sup>3</sup>                                       |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup>                                       |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> )        | 2 mg/m <sup>3</sup>                                       |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup>                                       |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (inhalable)                           |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )            | 1 mg/m <sup>3</sup>                                       |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> )        | 3 mg/m <sup>3</sup> (inhalable fraction)                  |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )         | 1.5 mg/m <sup>3</sup> (inhalable fraction)                |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> )        | 3 mg/m <sup>3</sup>                                       |
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup>                                       |
| <b>Silver (7440-22-4)</b>          |                                      |   |
| <b>Mexico</b>                      | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup>                                     |
| <b>USA ACGIH</b>                   | ACGIH TWA (mg/m <sup>3</sup> )       | 0.1 mg/m <sup>3</sup> (dust and fume)                     |
| <b>USA OSHA</b>                    | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 0.01 mg/m <sup>3</sup>                                    |
| <b>USA NIOSH</b>                   | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.01 mg/m <sup>3</sup> (dust)                             |
| <b>USA IDLH</b>                    | US IDLH (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (dust)                               |
| <b>Alberta</b>                     | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup>                                     |
| <b>British Columbia</b>            | OEL STEL (mg/m <sup>3</sup> )        | 0.03 mg/m <sup>3</sup>                                    |
| <b>British Columbia</b>            | OEL TWA (mg/m <sup>3</sup> )         | 0.01 mg/m <sup>3</sup>                                    |
| <b>Manitoba</b>                    | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (dust and fume)                     |



# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                    |                               |                                       |
|------------------------------------|-------------------------------|---------------------------------------|
| <b>New Brunswick</b>               | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup>                 |
| <b>Newfoundland &amp; Labrador</b> | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (dust and fume) |
| <b>Nova Scotia</b>                 | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (dust and fume) |
| <b>Nunavut</b>                     | OEL STEL (mg/m <sup>3</sup> ) | 0.3 mg/m <sup>3</sup>                 |
| <b>Nunavut</b>                     | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup>                 |
| <b>Northwest Territories</b>       | OEL STEL (mg/m <sup>3</sup> ) | 0.3 mg/m <sup>3</sup>                 |
| <b>Northwest Territories</b>       | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup>                 |
| <b>Ontario</b>                     | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (dust and fume) |
| <b>Prince Edward Island</b>        | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup> (dust and fume) |
| <b>Québec</b>                      | VEMP (mg/m <sup>3</sup> )     | 0.1 mg/m <sup>3</sup>                 |
| <b>Saskatchewan</b>                | OEL STEL (mg/m <sup>3</sup> ) | 0.3 mg/m <sup>3</sup>                 |
| <b>Saskatchewan</b>                | OEL TWA (mg/m <sup>3</sup> )  | 0.1 mg/m <sup>3</sup>                 |
| <b>Yukon</b>                       | OEL STEL (mg/m <sup>3</sup> ) | 0.03 mg/m <sup>3</sup>                |
| <b>Yukon</b>                       | OEL TWA (mg/m <sup>3</sup> )  | 0.01 mg/m <sup>3</sup>                |

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective clothing. Gloves. Safety glasses. Dust formation: dust mask. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. With molten material wear thermally protective clothing.

**Hand Protection:** Wear chemically resistant protective gloves. If material is hot, wear thermally resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Wear suitable protective clothing. Wash contaminated clothing before reuse.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|                                 |                                    |
|---------------------------------|------------------------------------|
| Physical State                  | : Solid                            |
| Appearance                      | : Metallic                         |
| Odor                            | : Odorless                         |
| Odor Threshold                  | : Not available                    |
| pH                              | : Not available                    |
| Evaporation Rate                | : Not available                    |
| Melting Point                   | : 440 - 1215 °F (226.7 - 657.2 °C) |
| Freezing Point                  | : Not available                    |
| Boiling Point                   | : Not available                    |
| Flash Point                     | : Not applicable                   |
| Auto-ignition Temperature       | : Not available                    |
| Decomposition Temperature       | : Not available                    |
| Flammability (solid, gas)       | : Not available                    |
| Lower Flammable Limit           | : Not available                    |
| Upper Flammable Limit           | : Not available                    |
| Vapor Pressure                  | : Not available                    |
| Relative Vapor Density at 20 °C | : Not available                    |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|  |   |
|--|---|
| <b>Relative Density</b>                                  | : Not available   |
| <b>Specific Gravity</b>                                  | : 2.5 - 2.9   |
| <b>Solubility</b>  | : Insoluble in water  |
| <b>Partition Coefficient: N-octanol/water</b>            | : Not available   |
| <b>Viscosity</b>   | : Not available   |
| <b>Explosion Data – Sensitivity to Mechanical Impact</b> | : Not expected to present an explosion hazard due to mechanical impact. |
| <b>Explosion Data – Sensitivity to Static Discharge</b>  | : Not expected to present an explosion hazard due to static discharge.  |

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Avoid creating or spreading dust. Sparks, heat, open flame and other sources of ignition.
- 10.5. Incompatible Materials:** When molten: water. Strong acids, strong bases, strong oxidizers. Alkalis. Metal oxides. Moisture. Corrosive substances in contact with metals may produce flammable hydrogen gas.
- 10.6. Hazardous Decomposition Products:** Oxides of iron and carbon. Organic acid vapors. With acids, aluminum metals, or ammonium salts may react to form toxic vapors. May form solid compounds releasing heat. Lead compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified.

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified.

**Respiratory or Skin Sensitization:** Not classified. Not classified.

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified.

**Reproductive Toxicity:** Not classified.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Dust from physical alteration of this product causes skin irritation. Causes severe skin burns. Contact with fumes or metal powder will irritate skin. Contact with hot, molten metal will cause thermal burns. Dust may cause irritation in skin folds or by contact in combination with tight clothing. Mechanical damage via flying particles and chipped slag is possible.

**Symptoms/Injuries After Eye Contact:** Dust may cause mechanical irritation to eyes, nose, throat, and lungs.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** In massive form, no hazard exists. If physically altered to present slivers, ribbons, dusts or fumes from molten material: Aluminum: Inhalation of finely divided aluminum powder may cause pulmonary fibrosis. Inhalation of Nickel compounds has been shown in studies to provide an increased incidence of cancer of the nasal cavity, lung and possibly larynx in nickel refinery workers. Nickel: May cause a form of dermatitis known as nickel itch and intestinal irritation, which may cause disorders, convulsions and asphyxia. Manganese: Chronic exposure can cause inflammation of the lung tissue, scarring the lungs (pulmonary fibrosis). Copper: Overexposure to fumes may cause metal fume fever (chills, muscle aches, nausea, fever, dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair. Tissue damage of mucous membranes may follow chronic dust exposure. Silicon: Can cause chronic bronchitis and narrowing of the airways. Lead: Exposure can result in lassitude (weakness, exhaustion), insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Zinc: Prolonged exposure to high concentrations of zinc fumes may cause "zinc shakes", an involuntary twitching of the muscles. Otherwise, zinc is non-toxic. Tin: Has been shown to increase incidence of sarcoma in animal tests. Chronic exposure to tin dusts and fume may result in "stannosis", a mild form of pneumoconiosis. Silver:

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Chronic skin contact or ingestion of silver dust, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

|  |  |
|--|--|
| <b>Cobalt (7440-48-4)</b>              |  |
| LD50 Oral Rat                          | 215.9 - 1140 mg/kg                             |
| LC50 Inhalation Rat                    | > 10 mg/l (Exposure time: 1 h)                 |
| ATE US (dust, mist)                    | 0.01 mg/l/4h                                   |
| <b>Zinc oxide (1314-13-2)</b>          |  |
| LD50 Oral Rat                          | > 5000 mg/kg                                   |
| LD50 Dermal Rat                        | > 2000 mg/kg                                   |
| <b>Tin (7440-31-5)</b>                 |  |
| LD50 Oral Rat                          | 700 mg/kg                                      |
| <b>Manganese (7439-96-5)</b>           |  |
| LD50 Oral Rat                          | > 2000 mg/kg                                   |
| <b>Lead (7439-92-1)</b>                |  |
| ATE US (oral)                          | 500.00 mg/kg body weight                       |
| ATE US (dust, mist)                    | 1.50 mg/l/4h                                   |
| <b>Nickel (7440-02-0)</b>              |  |
| LD50 Oral Rat                          | > 9000 mg/kg                                   |
| <b>Silver (7440-22-4)</b>              |  |
| LD50 Oral Rat                          | > 2000 mg/kg                                   |
| <b>Cobalt (7440-48-4)</b>              |  |
| IARC Group                             | 2B   |
| <b>Lead (7439-92-1)</b>                |  |
| IARC Group                             | 2A   |
| National Toxicity Program (NTP) Status | Reasonably anticipated to be Human Carcinogen. |
| <b>Nickel (7440-02-0)</b>              |  |
| IARC Group                             | 2B   |
| National Toxicity Program (NTP) Status | Reasonably anticipated to be Human Carcinogen. |

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity No additional information available

|                                |   |
|--------------------------------|---|
| <b>Copper (7440-50-8)</b>      |   |
| LC50 Fish 1                    | <= 0.0068 (0.0068 - 0.0156) mg/l (Exposure time: 96 h - Species: Pimephales promelas)                   |
| EC50 Daphnia 1                 | 0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])                                       |
| EC50 Other Aquatic Organisms 1 | 0.0426 (0.0426 - 0.0535) mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static]) |
| LC 50 Fish 2                   | 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])                                  |
| EC50 Other Aquatic Organisms 2 | 0.031 (0.031 - 0.054) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])    |
| <b>Cobalt (7440-48-4)</b>      |   |
| LC50 Fish 1                    | 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])                                    |
| <b>Zinc oxide (1314-13-2)</b>  |   |
| LC50 Fish 1                    | 780 µg/l (Exposure time: 96 h - Species: Pimephales promelas)   |
| EC50 Daphnia 1                 | 0.122 mg/l  |
| NOEC chronic fish              | 0.026 mg/l (Species: Jordanella floridae)   |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|                                       |  |
|---------------------------------------|--|
| <b>Manganese (7439-96-5)</b>          |  |
| <b>NOEC chronic fish</b>              | 3.6 mg/l (Exposure time: 96h; Species: Oncorhynchus mykiss)  |
| <b>Lead (7439-92-1)</b>               |  |
| <b>LC50 Fish 1</b>                    | 0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])                             |
| <b>EC50 Daphnia 1</b>                 | 600 µg/l (Exposure time: 48 h - Species: water flea)   |
| <b>LC 50 Fish 2</b>                   | 1.17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])                        |
| <b>Nickel (7440-02-0)</b>             |  |
| <b>LC50 Fish 1</b>                    | 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)  |
| <b>EC50 Daphnia 1</b>                 | 13 (13 - 200) µg/l (Exposure time: 48h - Species: Ceriodaphnia dubia [static])                       |
| <b>LC 50 Fish 2</b>                   | 1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])                              |
| <b>EC50 Daphnia 2</b>                 | 1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])                                       |
| <b>EC50 Other Aquatic Organisms 2</b> | 0.174 (0.174 - 0.311) mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static]) |
| <b>Silver (7440-22-4)</b>             |  |
| <b>LC50 Fish 1</b>                    | 0.00155 (0.00155 - 0.00293) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])       |
| <b>EC50 Daphnia 1</b>                 | 0.00024 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])                                 |
| <b>LC 50 Fish 2</b>                   | 0.0062 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])                      |

### Persistence and Degradability

|                                      |                            |
|--------------------------------------|----------------------------|
| <b>Aluminum Alloys</b>               |                            |
| <b>Persistence and Degradability</b> | Not established.           |
| <b>Copper (7440-50-8)</b>            |                            |
| <b>Persistence and Degradability</b> | Not readily biodegradable. |

### 12.3. Bioaccumulative Potential

|                                  |                      |
|----------------------------------|----------------------|
| <b>Aluminum Alloys</b>           |                      |
| <b>Bioaccumulative Potential</b> | Not established.     |
| <b>Cobalt (7440-48-4)</b>        |                      |
| <b>BCF Fish 1</b>                | (no bioaccumulation) |

### 12.4. Mobility in Soil

Not available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Treatment Methods:** Recycle product or dispose properly.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

## SECTION 14: TRANSPORT INFORMATION

- 14.1. **In Accordance with DOT** Not regulated for transport
- 14.2. **In Accordance with IMDG** Not regulated for transport
- 14.3. **In Accordance with IATA** Not regulated for transport
- 14.4. **In Accordance with TDG** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

|   |                                 |
|---|---------------------------------|
| <b>Aluminum Alloys</b>  |                                 |
| <b>SARA Section 311/312 Hazard Classes</b>                                | Delayed (chronic) health hazard |
| <b>Aluminum (7429-90-5)</b>   |                                 |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |                                 |
| Listed on United States SARA Section 313                                  |                                 |
| <b>SARA Section 313 - Emission Reporting</b>                              | 1.0 % (dust or fume only)       |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|   |  |
|---|--|
| <b>Silicon (7440-21-3)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| <b>Copper (7440-50-8)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>SARA Section 313 - Emission Reporting</b>                              | 1.0 %  |
| <b>Cobalt (7440-48-4)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>SARA Section 313 - Emission Reporting</b>                              | 0.1 %  |
| <b>Zinc oxide (1314-13-2)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| <b>Tin (7440-31-5)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| <b>Manganese (7439-96-5)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>SARA Section 313 - Emission Reporting</b>                              | 1.0 %  |
| <b>Lead (7439-92-1)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>SARA Section 313 - Emission Reporting</b>                              | 0.1 %  |
| <b>Nickel (7440-02-0)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>      | 100 lb (only applicable if particles are < 100 µm) |
| <b>SARA Section 313 - Emission Reporting</b>                              | 0.1 %  |
| <b>Silver (7440-22-4)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |  |
| Listed on United States SARA Section 313                                  |  |
| <b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>      | 1000 lb < 100 um CERCLA/SARA RQ CHANGE TITLE       |
| <b>SARA Section 313 - Emission Reporting</b>                              | 1.0 %  |

### 15.2. US State Regulations

|  |  |
|--|--|
| <b>Cobalt (7440-48-4)</b>  |  |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>               | WARNING: This product contains chemicals known to the State of California to cause cancer.                     |
| <b>Lead (7439-92-1)</b>  |  |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>               | WARNING: This product contains chemicals known to the State of California to cause cancer.                     |
| <b>U.S. - California - Proposition 65 - Developmental Toxicity</b>         | WARNING: This product contains chemicals known to the State of California to cause birth defects.              |
| <b>U.S. - California - Proposition 65 - Reproductive Toxicity - Female</b> | WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm. |
| <b>U.S. - California - Proposition 65 - Reproductive Toxicity - Male</b>   | WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.   |
| <b>Nickel (7440-02-0)</b>  |  |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>               | WARNING: This product contains chemicals known to the State of California to cause cancer.                     |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|  |
|--|
| <b>Aluminum (7429-90-5)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Silicon (7440-21-3)</b>   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List  |
| <b>Copper (7440-50-8)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Cobalt (7440-48-4)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Zinc oxide (1314-13-2)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Tin (7440-31-5)</b>   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List  |
| <b>Manganese (7439-96-5)</b>   |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Lead (7439-92-1)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |
| <b>Nickel (7440-02-0)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances<br>U.S. - Pennsylvania - RTK (Right to Know) List |
| <b>Silver (7440-22-4)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) List   |

### 15.3. Canadian Regulations

|                        |
|------------------------|
| <b>Aluminum Alloys</b> |
|------------------------|

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|   |   |
|---|---|
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Aluminum (7429-90-5)</b>                             |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Class B Division 6 - Reactive Flammable Material<br>Class B Division 4 - Flammable Solid  |
| <b>Silicon (7440-21-3)</b>                              |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Copper (7440-50-8)</b>                               |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Cobalt (7440-48-4)</b>                               |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 0.1 %                                 |   |
| WHMIS Classification                                    | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| <b>Zinc oxide (1314-13-2)</b>                           |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Tin (7440-31-5)</b>                                  |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Manganese (7439-96-5)</b>                            |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria   |
| <b>Lead (7439-92-1)</b>                                 |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 0.1 %                                 |   |
| WHMIS Classification                                    | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  |
| <b>Nickel (7440-02-0)</b>                               |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 0.1 %                                 |   |
| WHMIS Classification                                    | Class D Division 2 Subdivision B - Toxic material causing other toxic effects   |
| <b>Silver (7440-22-4)</b>                               |   |
| Listed on the Canadian DSL (Domestic Substances List)   |   |

# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|   |   |
|---|---|
| Listed on the Canadian IDL (Ingredient Disclosure List) |   |
| IDL Concentration 1 %                                   |   |
| WHMIS Classification                                    | Uncontrolled product according to WHMIS classification criteria |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 12/15/2014  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

|  |   |
|--|---|
| Acute Tox. 1<br>(Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 1                                    |
| Acute Tox. 4<br>(Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4                                    |
| Acute Tox. 4 (Oral)                    | Acute toxicity (oral) Category 4  |
| Aquatic Acute 1                        | Hazardous to the aquatic environment - Acute Hazard Category 1                      |
| Aquatic Acute 3                        | Hazardous to the aquatic environment - Acute Hazard Category 3                      |
| Aquatic Chronic 1                      | Hazardous to the aquatic environment - Chronic Hazard Category 1                    |
| Aquatic Chronic 3                      | Hazardous to the aquatic environment - Chronic Hazard Category 3                    |
| Carc. 1B                               | Carcinogenicity Category 1B   |
| Carc. 2                                | Carcinogenicity Category 2  |
| Comb. Dust                             | Combustible Dust  |
| Eye Irrit. 2A                          | Serious eye damage/eye irritation Category 2A                                       |
| Flam. Sol. 1                           | Flammable solids Category 1   |
| Repr. 1A                               | Reproductive toxicity Category 1A   |
| Repr. 2                                | Reproductive toxicity Category 2  |
| Resp. Sens. 1B                         | Respiratory sensitisation Category 1B   |
| Skin Sens. 1                           | Skin sensitization Category 1   |
| STOT RE 1                              | Specific target organ toxicity (repeated exposure) Category 1                       |
| STOT SE 3                              | Specific target organ toxicity (single exposure) Category 3                         |
| Water-react. 2                         | Substances and mixtures which in contact with water emit flammable gases Category 2 |
| H228                                   | Flammable solid   |
|  | May form combustible dust concentrations in air                                     |
| H261                                   | In contact with water releases flammable gases                                      |
| H302                                   | Harmful if swallowed  |
| H317                                   | May cause an allergic skin reaction   |
| H319                                   | Causes serious eye irritation   |
| H330                                   | Fatal if inhaled  |
| H332                                   | Harmful if inhaled  |
| H334                                   | May cause allergy or asthma symptoms or breathing difficulties if inhaled           |
| H335                                   | May cause respiratory irritation  |
| H350                                   | May cause cancer  |
| H351                                   | Suspected of causing cancer   |
| H360                                   | May damage fertility or the unborn child  |
| H361                                   | Suspected of damaging fertility or the unborn child                                 |
| H372                                   | Causes damage to organs through prolonged or repeated exposure                      |
| H400                                   | Very toxic to aquatic life  |
| H402                                   | Harmful to aquatic life   |



# Aluminum Alloys

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

|      |  |
|------|--|
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects    |

### Party Responsible for the Preparation of This Document

Ductmate Industries Inc  
210 5th Street  
Charleroi, PA  
15022  
TEL: 1-800-245-3188

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2