

D U C T M A T E

S.L.S.™



Super Liner Seal



Premium Quality

- Flame resistant
- Moisture resistant
- Exceptional coverage
- Good dry time
- Wipes clean with water
- Durable finish
- Compliant with LEED® EQ, Credit 4.1 VOC Content
- Manufactures by S.M.W.I.A. Local 12



DUCTMATE®
Industries, Inc.

DESCRIPTION

S.L.S. is a high viscosity, premium quality, water based fiberglass encapsulated coating specifically formulated for spray applications. Formulated with EPA Registered preservatives which prevent the growth of mold, mildew, fungus, bacteria, and yeast.

BASIC USE

S.L.S. is used to encapsulate fiberglass duct and duct insulation, eliminating airborne fibers, the leading contributor to poor indoor air quality.

APPLICATION

Applied by standard spray equipment. All surfaces should be dry prior to application. Apply directly to the surface of fibrous duct insulation. **Do not thin.**

SPECIAL CHARACTERISTICS

- Moisture resistant
- Water cleanup of tools and equipment
- Good dry time
- Exceptional coverage
- Compliant with LEED® EQ. Credit 4.1 VOC Content

PACKAGING INFORMATION

Part No.	Description	Quantities & Weights
SLS5	5 Gallon	1 - 5 gal pail @ 45 lbs./pail
SLS54	54 Gallon	1 - 54 gal drum @ 494 lbs./drum

LIMITED PRODUCT WARRANTY

Ductmate warrants that S.L.S., when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at the time of sale. Ductmate's warranty shall run for a period of one year from the date of manufacture.

Warranty Limitation

The warranty stated above is in lieu of all other warranties, express or implied, including but not limited to the implied warranties of MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Although Ductmate may have suggested the product, or provided written or oral advice to the Purchaser, it is the Purchaser's responsibility to test and determine the suitability of S.L.S., for the intended use and purpose, and Purchaser and/or its customer assumes all risk and liability whatsoever regarding such suitability.

Limitation of Liability

In the event of a breach of the above warranty, Ductmate's sole obligation, and Purchaser's sole and exclusive remedy, shall be, at Ductmate's option, repair or replacement of any defective products, or refund of an applicable portion of the purchase price. Ductmate shall have no liability for costs of removal or reinstallation of the product. The Purchaser agrees that no other remedy, including but not limited to loss of profits, loss sales, injury to person or property, or any other special, incidental or consequential damages, shall be available to the Purchaser for any claim arising out of this Agreement, regardless of whether such claim is made in contract or in tort, including strict liability in tort. In no event will Ductmate be obligated to pay damages to the Purchaser in any amount exceeding the purchase price that the Purchaser paid to Ductmate for the allegedly defective product.

TECHNICAL INFORMATION

BASE:	Synthetic Latex
COLOR:	Off white
SOLVENT:	Water
WEIGHT PER GALLON:	10.75 ± 0.5 lbs./gal
SOLIDS:	54 ± 2%
VISCOSITY:	15,000 cps ± 2,000 cps
APPLICATION TEMPERATURE:	40°F to 90°F
STORAGE TEMPERATURE:	40°F to 90°F
DRY TIME/TACK FREE:	4 Hours (ASTM C679) depending on temperature, humidity and application thickness 24-72 Hours fully cured.
FLAMMABILITY:	None
FLASH POINT:	No Flash to Boiling
COVERAGE:	Approximately 200 ft. ² /gal depending on application technique
FREEZE THAW STABILITY:	5 cycles
SHELF LIFE:	1 year (unopened container)
PACKAGING:	Available in 5 or 54 gallons

SURFACE BURNING CHARACTERISTICS UL 723

Applied to Inorganic Reinforced Cement Board +

FLAME SPREAD 0
SMOKE DEVELOPED 0

± Tested as applied in two 2 in. wide strips 8 in. on center covering 22.2 percent of the test sample area at a coverage rate of 200 sq. ft. per gallon.

ULC S102.2

APPLIED TO INORGANIC REINFORCED CEMENT BOARD +

FLAME SPREAD 0
SMOKE DEVELOPED 0

± Tested as applied in two 50 mm wide strips space 200 mm on center (covering 22.6 % of the exposed test sample area) at a coverage of 5 m²/L.



Charleroi, PA **Lodi, CA**
210 Fifth Street 810 S. Cluff Avenue
Charleroi, PA 15022 Lodi, CA 95240-9141
724-258-0500 209-333-4680

*Additional Manufacturing and Warehousing in
Monongahela, PA and Wagoner, OK*

1-800-245-3188 • www.ductmate.com

© Copyright Ductmate Industries, Inc. All rights reserved.



Ductmate Is A Proud Member Of The Following Organizations:



Distributed By: